

**KANSAS DEPARTMENT OF TRANSPORTATION
SPECIAL PROVISION TO THE
STANDARD SPECIFICATIONS, 2007 EDITION**

SECTION 904

MULCHING

Page 900-11, delete subsection 904.4c. and replace with the following:

c. Payment. Payment for "Mulching (Temporary)", "Mulching Tacking Slurry" and "Mulching (Hydro)" at the contract unit prices is full compensation for the specified work.

When temporary seeding and permanent seeding are combined, the Engineer will pay for mulching under the bid item Mulching (Temporary), and the bid item Mulching (Permanent) (Set Price) will be underrun.

When the quantity of "Mulching Tacking Slurry" overruns or underruns the contract quantity by any amount, the contract unit price shall govern.

Payment for "Mulching (Permanent) (Set Price)" at the contract set unit price (subject to the adjustments in **TABLE 904-1**) is full compensation for the specified work.

TABLE 904-1: PERMANENT MULCHING PAYMENT	
Mulching (Permanent) Quantity, M (acres)	Percent of Contract Set Unit Price Per Acre
$M \leq 15$	100%
$15 < M \leq 30$	90%
$30 < M$	80%

Page 900-10, delete subsections 904.3b. and replace with the following:

b. Mulching Tacking Slurry. Place and punch the mulch immediately after the fertilizing and seeding operations.

A sufficient length of mulching material is needed for the mulch to interlap and bind together. Short stemmed mulching material is more vulnerable to wind action. When the mulching is applied with a straw blower, if required, remove the cutting knives to prevent cutting the mulch too short.

After an area is fertilized and seeded, uniformly spread the mulch over the area. Apply the mulch at the rates shown in the Contract Documents. The rates shown in the Contract Documents are a guide, the Engineer will determine if the applied mulch is sufficient to protect the seeded area.

After the mulch is applied to an area, punch the mulching material (except wood chips and excelsior material) approximately 2 inches into the ground. Perform the punching operation longitudinally, using a mulch puncher. When needed, use weights on the mulch puncher to punch the mulching material into the soil.

When the slope is too steep to use a mulch puncher, "pat" the mulch with forks as it is placed on the slope. To reduce wind loss, cover the mulch on the upper 1/3 of slope by hand spreading a light application of soil or sand on the mulch.

On lawns and small areas in urban areas, apply the mulch material using hand methods, unless otherwise approved by the Engineer. As the mulch is placed, "pat" the mulch with a fork. To reduce wind loss, hand spread a light application of soil or sand over the mulched area.

Immediately after the designated areas are mulched and punched, use hydraulic slurry equipment to apply the mulching tacking slurry. Unless shown otherwise in the Contract Documents, apply the mulching tacking slurry at the rate of 900 pounds per acre. Distribute the mulching tacking slurry uniformly over the mulch, leaving no bare spots. Arrange work so the mulching tacking slurry can be placed within 24 hours after each area has been mulched.