

841 - LIGHT TYPE SURFACING

SECTION 841

LIGHT TYPE SURFACING

841.1 DESCRIPTION

Haul the material shown in the Contract Documents to the roadway and windrow the material for surfacing.

BID ITEM

Light Type Surfacing (*)
Type: SA- or SS-*

UNITS

Cubic Yard

841.2 MATERIALS

Provide the specified type of aggregate that complies with **DIVISION 1100**.

841.3 CONSTRUCTION REQUIREMENTS

When shown in the Contract Documents, prepare the embankment or subgrade as detailed in the Contract Documents. When not shown in the Contract Documents, others will prepare the embankment or subgrade.

The rate of application for the light type surfacing is shown in the Contract Documents.

Do not haul material to the road when weather or road conditions are such that the hauling operations will damage the roadbed or subgrade.

Windrow the material hauled to the road along one shoulder of the road. Place the windrow on the roadway and parallel to the edge of the roadway, approximately 1 foot from the edge of the roadway or as directed by the Engineer. Construct a uniform windrow to a maximum width of 6 feet.

When not shown in the Contract Documents, others will spread the light type surfacing. When shown in the Contract Documents, spread the light type surfacing to the dimensions shown in the Contract Documents.

841.4 MEASUREMENT AND PAYMENT

The Engineer will measure the light type surfacing by the cubic yard.

Payment for "Light Type Surfacing" at the contract unit price is full compensation for the specified work.