

**KANSAS DEPARTMENT OF TRANSPORTATION
SPECIAL PROVISION TO THE
STANDARD SPECIFICATIONS, 2015 EDITION**

Delete SECTION 1304 and replace with the following:

SECTION 1304

SOLID CONCRETE INTERLOCKING PAVING BRICKS

1304.1 DESCRIPTION

This specification covers solid interlocking paving units (paving bricks) made from portland cement, blended hydraulic cement, or supplementary cementitious materials plus water, and suitable normal weight mineral aggregates with or without the inclusion of other materials (i.e. admixtures and/or coloring pigments).

1304.2 REQUIREMENTS

Provide materials that comply with the applicable requirements.

- Fine Aggregate FA-A..... **DIVISION 1100**
- Concrete and Mortar..... **DIVISION 400**

Provide paving brick that complies with physical requirements of ASTM C 936 in the styles, dimensions and colors shown in the Contract Documents.

If specified, provide commercially available edging for edge restraints of the type and dimensions shown in the Contract Documents.

1304.3 METHODS OF TEST

Use the methods specified in ASTM C 936. Perform resistance to freeze-thaw testing using a 3% saline solution and freezing temperature corresponding to C 936, Appendix X1, Zone 3. The mass loss criteria of C 936, paragraph 5.5 apply.

1304.4 PREQUALIFICATION

None Required.

1304.5 BASIS OF ACCEPTANCE

Receipt and approval of a Type D certification as specified in **DIVISION 2600**.